

EU TYPE EXAMINATION CERTIFICATE

Certificate No: 2163-PPE-2435

DDK İŞ GÜVENLİK BİRİMİ EKİPMANLARI TEKSTİL EĞİTİM İNŞAAT TAAHHÜT
TİCARET ve SANAYİ LİMİTED ŞİRKETİ

Fevziçakmak Mahallesi 10637. Sokak. No:23, 42050 Karatay Konya, Türkiye

It is certified that the manufacturer's technical file (Dated 19.08.2024) and the PPE product, detailed below, have been assessed and found to meet the applicable Essential Health and Safety Requirements in Annex II of Regulation (EU) 2016/425 based on the evaluation on technical documentation and relevant test reports.

Identification of the Personal Protective Equipment

Product Identification	: Occupational Footwear
Outsole Structure	: Moulded
Outsole	: PU
Upper	: PU
Size	: EUR 36 - 49
Class	: Class II
Brand Name	: DDK
Type/Model	: Troya Boots O4, PU0104405 (Design C), PU010440 (Design D)
Variants	: Upper Colour (Khaki, White, Red, Orange, Black, Yellow, Navy Blue), Sole Colour (Black, Navy Blue)
Category	: O4
Additional Requirements	: SR, CI, FO
PPE Category	: II

Details are provided in annex 2163-PPE-2435-1 of this certificate.

The following harmonised standard have been applied:

EN ISO 20347:2022 Personal Protective Equipment - Occupational Footwear

Here by the manufacturer is allowed to fix CE mark on the Category II product models given above, with the below requirements under responsibility of the manufacturer;

- Issuing an appropriate EU Declaration of Conformity according to **Personal Protective Equipment Regulation (EU) 2016/425 Annex 9**.
- Ongoing successful performance in fulfilment of the requirements set out in **Personal Protective Equipment Regulation (EU) 2016/425** and harmonised standards, according to **Annex 6 (Module C)** of the regulation

This certificate is initially issued on **20.08.2024** and will be valid for 5 years from the initial issue date, if there is no change in the design of the product, relevant harmonised standards and regulation.



Suat KAÇMAZ

UNIVERSAL CERTIFICATION
Director

UNIVERSALCERT.COM



Annex 2163-PPE-2435-1

PRODUCT PHOTOS



UPPER (PU)

Height: Min Design C: 162 mm, Design D: 255mm
Thickness: Min 1 mm
Tensile properties: Modulus at 100 % elongation, Min 1 N/mm²
Elongation at break, Min 250%
Flexing resistance: no cracking before 150 000 flex cycles
Resistance to hydrolysis: no cracking before 150 000 flex cycles

INSOCK (Textile coated PU)

Abrasion Resistance: No holes before, Dry Min 25600, Wet Min 12800 cycles
Water Absorption: Min 70 mg/cm²,
Water Desorption: Min 80%
Thickness: Min 2 mm

OUTSOLE (PU - Density: > 0.9g/cm³)

Thickness: Outsole without cleats, min 3 mm
Cleat Height: Min 4 mm
Tear Strength: Min 8 kN/m
Abrasion Resistance: Max 150 mm³
Flexing Resistance: Max 4 mm cut growth before 30,000 cycles
Hydrolysis: Max 6mm cut growth before 150,000 cycles
Slip resistance on ceramic with NaLS solution: forward heel slip \geq 0,31 - backward forepart slip \geq 0,36
Upper/outsole bond strength: Min 4 N/mm
Electrical properties (Antistatic): Min 100 k Ω , Max 1000 M Ω
Energy absorption of seat region: Min 20 J

MARKING



CE EN ISO 20347 : 2022 O4 SR CI FO

www.ddkisguvenligi.com.tr

Credit Ali Paşa Mah. Seymen Yolu Cad. No:9/1

Marmaraereğlisi - Tekirdağ TURKEY




Suat KAÇMAZ

UNIVERSAL CERTIFICATION
Director



UNIVERSALCERT.COM

